


4

З

• •



| REV | ZONE | REVISION | DATE | ECN | NAME | CHKD |
|-----|---------|--|----------|----------------|------|------|
| A-1 | ALL | SUBMITTAL DRAWINGS | 4/23/13 | PXEC0032 | RK | AEK |
| B-I | ALL | RELEASE FOR PRODUCTION | 04/23/13 | PXEC0032 | RK | AEK |
| C-I | 2,3 ALL | CONVERT TO POWEREX DRYER | 2/20/14 | PXEC0074 | RK | AEK |
| D-I | 2,3 ALL | UPDATED DRYER OUTLET ORIENTATION | 4/1/15 | PXEC0100 | AEK | GES |
| E | ALL | ADDED GAUGE AND BRACKET | 6/20/19 | PXEC0273 | MAH | SJA |
| F | ALL | CHANGED TO TRIDENT DRYERS, MORGANTON TANK, UPDATED TO TC | 9/10/19 | PXEC0230, 0291 | RJH | GES |


| POWER | IN |
|-------|----|
|-------|----|

| SYMBOL LEGEND ⊖ = MINUS DRAFT ⊕ = PLUS DRAFT | AL CONTROL HARDNESS | Drawings to conform to the current revision of the following ANSI standards. Y14.3 Multi and sectional view dwgs. Y14.5M Dimensioning and tolerancing | | | | |
|---|--|---|------------------------------------|-----------|--------------|---|
| TOLERANCES NOT SPECIFIED . XX ± | | | e drawing | FOR DIMEN | SIONS | |
| . XXX ± Z (DEG.) ± | INCH | Sheet 1 d | of 4 | SCALE | 1:10 | A |
| CONFIDENTIAL DISCLO This drawing is the pro POWEREY INC of the SCOIT FE | DRAWN BY | CHECKED BY | APPROVED BY ENGINEERING | MFG/MRKTG | | |
| and subject to return on contents are confidential ar | POWEREX,INC.of the SCOTT FETZER COMPANY and subject to return on demand. Its contents are confidential and must not be | | AEK | JA | СТ | |
| copied or submitted to outsi use or examinatio | | 4/23/13 | 4/23/13 | 4/23/13 | 4/23/13 | |
| MATERIAL N/A | | | OW | | EX | |
| BART NAME 30HP ENCLOSED SCROLL | | | JCTION DRIVE, H4 8-769-7979 FAX | | | |
| | | DWG NO | | | SIZE | |
| 200GAL DUAL DESICCANT | LAB PACKAGE | | _SE30 | 05 | | |
| 2 | | | | | LSE3005. dwg | - |

D

С

В



8

7

6

5

4

4

З

5

| SHEET 2 – AIR TREATMENT LAYOUT SHEET 3 – PLAN VIEW SHEET 4 – FLOW SCHEMATIC | | | | | | | |
|---|----------------------------------|-----------------|---|----------------------------|---------------|--|--|
| SYMBOL LEGEND⇒ADDITIONAL CONTROLDrawings to conform to the current revision of the follo ANSI standards.⊕ = PLUS DRAFT⊕ = BRINELL HARDNESSY14.3 Multi and sectional view of Y14.5 M Dimensioning and tolerance | | | | following iew dwgs. | | | |
| TOLERANCES NOT SPECIFIED | AUTOCAD Rel2008 lt | DO NOT SCAL | .e drawing | FOR DIMEN: | SIONS | | |
| . XXX ± ∠(DEG.) ± | INCH | Sheet 2 | of 4 | 1:10 | | | |
| CONFIDENTIAL DISCL This drawing is the pr POWEREX, INC. of the SCOTT FI | operty of | DRAWN BY | CHECKED BY | APPROVED BY ENGINEERING | MFG/MRKTG | | |
| and subject to return on contents are confidential a copied or submitted to outsi use or examinati | nd must not be de parties for | RK 4/23/13 | AEK 4/23/13 | JA 4/23/13 | CT 4/23/13 | | |
| MATERIAL | | | | | EX | | |
| PART NAME | | | UCTION DRIVE, HA 38-769-7979 FAX: | | | | |
| 30HP ENCLOSED SC | DWG NO | 30 /077/7/7 FAX | | SIZE | | | |
| 200GAL DUAL DESICCANT | LAB PACKAGE | E LSE3005 D | | | | | |
| 2 | | | | | LSE3005. dwg | | |

NOTE:

I) SHEET I - SEH3007 LAYOUT

D


С

В

| ſ | 8 | 7 | | 6 | |
|---|------------------|---|------------------------|-----------|--|
| D | ELE CLEARANCE | I RECOMMENDED ECTRICAL PANEL E PER OSHA/NEC REQUIREMENTS | | | |
| | | | | | |
| С | | | | 24.00 | |
| | | | | | |
| В | | | | | |
| | | | | | |
| А | | MINIMUM REC MAINTENANCE | COMMENDED CLEARANCE | | |
| | 8 | 7 | | 6 | |

5

З



| REV | ZONE | REVISION | DATE | ECN | NAME | CHKD |
|-----|---------|--|----------|----------------|------|------|
| A-1 | ALL | SUBMITTAL DRAWINGS | 4/23/13 | PXEC0032 | RK | AEK |
| B-I | ALL | RELEASE FOR PRODUCTION | 04/23/13 | PXEC0032 | RK | AEK |
| C-I | 2,3 ALL | CONVERT TO POWEREX DRYER | 2/20/14 | PXEC0074 | RK | AEK |
| D-I | 2,3 ALL | UPDATED DRYER OUTLET ORIENTATION | 4/1/15 | PXEC0100 | AEK | GES |
| E | ALL | ADDED GAUGE AND BRACKET | 6/20/19 | PXEC0273 | MAH | SJA |
| F | ALL | CHANGED TO TRIDENT DRYERS, MORGANTON TANK, UPDATED TO TC | 9/10/19 | PXEC0230, 0291 | RJH | GES |

•


С

В

NOTE:

I) SHEET I - SEH3007 LAYOUT SHEET 2 - AIR TREATMENT LAYOUT SHEET 3 - PLAN VIEW SHEET 4 - FLOW SCHEMATIC

| $ \begin{array}{l} & \\ \Theta = \text{MINUS DRAFT} \\ \hline \Theta = \text{PLUS DRAFT} \\ \end{array} $ |) = ADDITIONA REQ'D > = BRINELL H | AL CONTROL HARDNESS | Drawings to current revi ANSI standar Y14.3 Multi ar Y14.5M Dimens | | | |
|---|---|------------------------------------|--|-----------|--------------|---|
| TOLERANCES NOT SPECIFIED | DO NOT SCAL | e drawing | FOR DIMEN | SIONS | | |
| . XXX ± ∠(DEG.) ± | INCH | Sheet 3 (| Sheet 3 of 4 Scale | | | A |
| CONFIDENTIAL DISCLE This drawing is the pro POWEREX.INC.of the SCOTT FE | DRAWN BY | CHECKED BY | APPROVED BY ENGINEERING | MFG/MRKTG | | |
| and subject to return on contents are confidential ar | RK | AEK | JA | СТ | | |
| copied or submitted to outsi use or examinatio | | 4/23/13 | 4/23/13 | 4/23/13 | 4/23/13 | |
| MATERIAL | | | | | FX | |
| PART NAME | 150 PREDU | JCTION DRIVE, H4 8-769-7979 FAX | ARRISON, OHIO 4 | L O O Y | | |
| 30HP ENCLOSED SC | DWG NO | | | SIZE | | |
| 200GAL DUAL DESICCANT | LAB PACKAGE | | _SE30 | 05 | | |
| 2 | | | | | LSE3005. dwg | - |



RESERVE PRESS.

SWITCH

× .

ADD. HANG TAG IP638500AV

5

PRESS.

] × ^{1/4}" B.V.

-

PRESS.

RELIEF

140 PSI

200 GALLON AIR RECEIVER

↓ 1/2" B.V.

I/2" FNPT

TO FLOOR DRAIN

4

- ELECTRIC

1/2"

DRAIN

SET AT 90 PSIG

SET AT 90 PSIG

47

1-1/2"

47

-X B.V. MANUAL

PRESS

GAUGE

 $\langle \rangle$

SIGHT C

I/2" FNPT TO FLOOR DRAIN

GUAGE GAUGE 0-200 PSI 0-200 PSI (GA031400AV) (GA016701AV)

З

DEW

POINT


MONITOR

× I/4" B.V.

З

CO MONITOR

|/4" |X B.V.



DATE ECN NAME CHKD REVISION RELEASE FOR PRODUCTION 04/23/13 AF CONVERT TO POWEREX DRYER 2/20/14 AEK UPDATED DRYER OUTLET ORIENTATION 4/1/15 GES AFK ADDED GAUGE AND BRACKET 6/20/19 MAH SJA NGED TO TRIDENT DRYERS, MORGANTON TANK, UPDATED TO 9/10/19 GES

С

D